



PN-EN 13859-1:2014-06; PN-EN 13859-2:2014-06

Declaration of Performance

According to Annex III of Regulation (EU) No. 305/2011
Nr. DoP 3-1012015-09
for the product

PRIVATE LABEL 150 / SUPERNOVA 150

1. Product type: unique identification code of the product type	Nr. DoP 3-1012015-09
2. Type batch or serial number or any other element allowing identification of the construction product as required und article 11(4)	Example + (lot nr. see packaging)
3. Intended use or uses of the construction product in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer	Underlay for discontinuous roofing and as underlay for walls (roof underlay, vapour permeable, watertight, for the pitched roofing also fully sheathed, and as housewrap or fasade membrane
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required und article 11(2)	Eurosystem Polska Sp. z o.o. Sp. K. Wiejska 13 46-055 Przywory, Poland VAT PL9372516153
5. Contact address: Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in article 12 (2)	not relevant
6. AVCP: System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V	System 3 and 4
7. Notified body: In case of declaration of performance concerning a construction product covered by a armonized standard	EN 13859-1:2010 Flexible sheets for waterproofing – Definitions and characteristics of underlays – Part 1: Underlays for discontinuous +roofing EN 13859-2:2010 Flexible sheets for waterproofing – Definitions and characteristics of underlays – Part 2: Underlays for walls The following notified bodies have carried out the type approvals following System 3. Institut für textile Bau- und Umwelttechnik GmbH Institute for textile building and environment technology Gutenbergstr. 29, 48268 Greven, Germany, identification number: 0799
8. In case of declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not relevant

9. Declared performance

Characteristic	Harmonized technical specification	Values
Reaction to fire	PN-EN 13859-1:2014-06; PNt-EN 13859-2:2014-06	F
Resistance to water penetration	PN-EN 13859-1:2014-06; PN-EN 13859-2:2014-06	W1
Tensile strength MD	PN-EN 13859-1:2014-06; PN-EN 13859-2:2014-06	≥ 250 N/50 mm (+/-70 N/50 mm)
Tensile strength CD	PN-EN 13859-1:2014-06; PN-EN 13859-2:2014-06	≥ 160 N/50 mm (+/-70 N/50 mm)
Elongation MD	PN-EN 13859-1:2014-06; PN-EN 13859-2:2014-06	$\leq 80\%$
Elongation CD	PN-EN 13859-1:2014-06; PN-EN 13859-2:2014-06	$\leq 80\%$
Tearing Resistance MD	PN-EN 13859-1:2014-06; PN-EN 13859-2:2014-06	≥ 135 N (+/-80 N)
Tearing Resistance CD	PN-EN 13859-1:2014-06; PN-EN 13859-2:2014-06	≥ 175 N (+/-80 N)
Flexibility at low temperatures	PN-EN 13859-1:2014-06; PN-EN 13859-2:2014-06	at -30 °C Conforming
Artificial ageing by long term exposure to the combination of UV radiation and elevated temperature and heat	PN-EN 13859-1:2014-06; PN-EN 13859-2:2014-06	
Tensile strength MD change	PN-EN 13859-1:2014-06; PN-EN 13859-2:2014-06	<30%
Tensile strength CD change	PN-EN 13859-1:2014-06; PN-EN 13859-2:2014-06	<30%
Elongation MD change	PN-EN 13859-1:2014-06; PN-EN 13859-2:2014-06	$\leq 80\%$
Elongation CD change	PN-EN 13859-1:2014-06; PN-EN 13859-2:2014-06	$\leq 80\%$
Water vapour transmission properties	PN-EN 13859-2:2014-06	Sd=0,02m (+/-0,019m)

10. Declaration: the performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of Performance is issued under the sole responsibility of the manufacturer identified in point 4.

Marcin Świarta
President



Przywory, 01.01.2015 r.